## Top Trends in DNS Security

Dave Piscitello, ICANN Rod Rasmussen, Internet Identity

## Attacks against registration services

#### Forms of attack

- Socially engineer registrant or registrar staff
- Exploit vulnerabilities in registrar web applications
- Brute force authentication services

## Objectives

- Gain access to a domain registration account
- Modify DNS configuration to exploit name service
- Cause reputational harm or facilitate other attacks

### Relevant SSAC documents

- SAC028, Registrar Impersonation Phishing Attacks
- SAC040, Measures to protect against registration service exploitation or misuse (publication pending)

## Systemic abuse of registration services

- Criminals continue to find service providers to exploit heavily
  - Systematic testing of systems and responses
  - TLD, domain itself not important want access to DNS
  - Will only relent once policies/procedures to curb are put in place by the provider
- Supports worst types of attack sites
  - Use fast flux and other techniques to keep sites live
  - Most prolific spammers and highest victimizations
- Relevant APWG Documents (at http://apwg.org)
  - Anti-Phishing Best Practices Recommendations for Registrars
  - Global Phishing Survey: Domain Name Use and Trends

# DNS Wildcarding, Redirection, Synthesized Responses

- Return a positive response to a DNS query when a negative response is expected
  - Wildcards in TLD zone files (Sitefinder)
  - Response modification by entrusted DNS provider
  - "On the fly" modification of NXDOMAIN response
- Affects more than just web applications
  - Monitoring and management applications need to see errors
  - Zone authority loses control over delegated name space
- SSAC documents
  - SAC032, DNS Response Modification
  - SAC041, Recommendation to Prohibit use of Redirection and Synthesized Responses in New TLDs

## **Botnets**

- Global pandemic
  - Infections in every country
  - Conficker: Domain abuse in 100s of TLDs
- Malware removal is hard
  - Malware writers quickly modify malware and variants in response to security and DNS community actions
- Conficker operational response proved that botnet activity can be "contained"
  - Time to consider models in which security and DNS communities can be proactive as well as reactive

## Subdomain registration services

- Subdomain registration is popular in CCTLDs
  - Usually free or low cost hosting with DNS service
    - Format: registered-label<dot>domain<dot>tld
    - Example phish domains:
    - signin.ebay.pochta.ru, wellsfargo.ns8-wistee.fr
  - More than web
    - blogs, pictures, hosting, social networks and email
  - Operates outside ICANN or CC authority remit
    - No WHOIS, no zone file access, ad hoc suspension process

## Subdomain registration services

- Criminal use of subdomain services on the rise
  - Abusive subdomains nearly as prevalent as phish domains
    - 6,300+ subdomain sites/accounts on 480 unique second-level domains
    - Increased nearly 50% over 1H2008, adding 200+ new unique second-level domains
    - If we counted these as "domain names," they would represent 12% of all domains
  - Major impacts on specific TLD abuse levels
- Relevant APWG Documents (at http://apwg.org)
  - Making Waves in the Phisher' Safest Harbors: Exposing the Dark Side of Subdomain Registries
  - Global Phishing Survey: Domain Name Use and Trends

## APWG global phishing survey 2008-2H

- Phishers move from registrar to registrar, TLD to TLD, to exploit the best phishing "holes"
- Moving away from IP-based phishing
- Registry anti-abuse programs have an effect
- Of the 30,454 phishing domains, we identified 5,591 (18.5%) clearly registered by phishers.
  - Of those 5,591, only 1,053 domains contained a relevant brand name or misspelling. (Only 3.5% of all domains used for phishing.)
  - Majority of phishing sites set-up on compromised servers
- Phishers happy to use any domain name

# **Top 10 Phishing TLDs by Score**

(minimum 30,000 domains and 25 phish)

Rank	TLD	TLD Location	Unique Domain Names used for phishing 2H2008	Domains in registry in Dec 2008	Score: Phish per 10,000 domains 2H2008
1	ve	Venezuela	1,504	82,500	182.3
2	th	Thailand	88	39,880	22.1
3	bz	Belize	55	43,377	12.7
4	su	Soviet Union	76	85,119	8.9
5	ro	Romania	188	310,114	6.1
6	cl	Chile	116	232,897	5.0
7	kr	Korea	413	983,626	4.2
8	vn	Vietnam	37	92,992	4.0
9	ru	Russia	676	1,860,179	3.6
10	tw	Taiwan	144	406,669	3.5

# **Questions and Discussion**